



2m USB 3.2 Type A Cable, 5Gbps, Anthra Line

No.: 36752

USB Type A Male to A Male

Description

- Professional choice USB 3.2 Gen 1 Type A to A cable for commercial and high performance AV and IT installations
- SuperSpeed USB - supports data transfer speeds up to 5Gbps [USB 3.0, USB 3.1 Gen 1]
- Robust PVC housing, gold plated connectors and contacts
- Triple shielded cable, corrosion resistant tinned copper conductors
- 10 year warranty

The Anthra Line USB 3.2 Type A to A cables from Lindy's Cable Lines concept are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 3.2 cables are premium connections that feature triple shielded construction with tinned copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

USB bandwidths up to 5Gbps are supported for rapid transfer of large data volumes.

Anthra Line USB 3.2 Type A to A cables are available in the following lengths: 0.5m, 1m, 2m, 3m and 5m.

We have adapted the naming of our USB 3 cables to follow the updated USB specification.

USB 3.0 and USB 3.1 Gen 1 have been renamed to USB 3.2 Gen 1, supporting data transfer up to 5Gbps

USB 3.1 and USB 3.1 Gen 2 are now called USB 3.2 Gen 2, supporting data transfer rates up to 10 Gbps

USB 3.2 Gen 2x2 is a new standard, supporting data transfer rates up to 20 Gbps

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

Technical details

Connectors

- Connector A: USB 3.2 Type A Male
- Connector B: USB 3.2 Type A Male
- Housing Material: PVC
- Connector Plating: Gold Plated
- Pin Construction: Copper
- Pin Plating: Gold Plated
- Dimensions, [approx.] WxDxH: 15.5x35x7.8mm [0.61x1.38x0.31in]

Cable Construction

- Length: 2m [6.6ft]
- Standard: USB 3.2 Gen 1
- Colour: Black
- Type: Round
- Jacket Diameter: 5.5mm [0.22in]
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge Power: 24AWG
- Conductor Gauge Data: 28AWG
- Shielding: Aluminium Braid 85%

Specifications

- Supported Bandwidth: 5Gbps
- Maximum Resolution: -
- Nominal Attenuation: 0.5-5m: 0.5MHz-7.5GHz
- Minimum Bend Radius: 48mm [1.89in]
- Operating Temperature: 0°C - 60°C [32°F - 140°F]
- Storage Temperature: 0°C - 60°C [32°F - 140°F]

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: CE, UKCA, RoHS, REACH, UL

Purchasing Information

- No. 36752
- EAN: 4002888367523

This product is also available in other lengths

- 36750 - 0.5m [1.64ft]
- 36751 - 1m [3.28ft]
- 36752 - 2m [6.56ft]
- 36753 - 3m [9.84ft]
- 36754 - 5m [16.44ft]