ViewSonic VX2479-HD-PRO

Key **Features**

- SuperClear® IPS panel
- 180Hz Refresh rate delivers fluid visuals
- Rapid 1ms MPRT for crisp image
- AMD FreeSync™ eliminates screen tearing and reduce stuttering
- HDR10 Delivers Stellar Contrast and Color Accuracy



Product **Description**

The ViewSonic VX2479-HD-PRO is a versatile 24-inch Full HD monitor designed to elevate your visual experience,whether you're working or gaming. With a high 180Hz refresh rate and lightning-fast 1ms MPRT response time, thismonitor ensures smooth visuals and minimal input lag – ideal for gamers seeking a competitive advantage. Equippedwith SuperClear® IPS technology, it boasts wide viewing angles and breathtaking visuals, perfect for immersivegaming sessions, creative endeavors, and efficient office work. Beyond performance, the monitor's sleek designelevates your workspace aesthetics, combining form and function for a complete package.

Visit Us

www.viewsonic.com

1 of 2

CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS, CCC, China ROHS, China Energy Label

VX2479-HD-PRO x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMl Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1

Please dispose of in accordance with local, state or federal laws. *Warranty offered may differ from market to market

DISPLAY		POWER		GENERAL
Display Size (in.):	24	Eco Mode (Conserve):	17W	
Viewable Area (in.):	23.8	Eco Mode (optimized):	20W	Regulations:
Panel Type:	IPS Technology	Consumption (typical):	24W	
Resolution:	1920 x 1080	Consumption (max):	28W	
Resolution Type:	FHD (Full HD)	Voltage:	AC 100-240V	PACKAGE CONTENTS:
Static Contrast Ratio:	1,000:1 (typ)	Stand-by:	0.5W	
Dynamic Contrast Ratio:	50M:1	Power Supply:	External Power Adaptor	
High Dynamic Range:	HDR10	ADDITIONAL HARDWARE		Recycle/Disposal:
Light Source:	LED	Kensington Lock Slot:	1	
Brightness:	250 cd/m² (typ)	CONTROLS		Warranty:
Colors:	16.7M	Physical Controls:	Key 1 (favorite), Key 2, Key 3,	
Color Space Support:	8 bit (6 bit + FRC)	•	Key 4, Key 5 (power)	
Aspect Ratio:	16:9	On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu	
Response Time (MPRT):	1ms			
Viewing Angles:	178º horizontal, 178º vertical	OPERATING CONDITIONS		
Backlight Life (Hours):	30000 Hrs (Min)	Temperature:	32°F to 104°F (0°C to 40°C)	
Curvature:	Flat	Humidity (non-condensing):	20% to 90%	
Refresh Rate (Hz):	180	WALL MOUNT		
/ariable Refresh Rate	FreeSync	VESA Compatible:	100 x 100 mm	
Technology:	FreeSync	INPUT SIGNAL		
Blue Light Filter:	Yes	Frequency Horizontal:	30 ~ 202KHz	
Flicker-Free:	Yes	Frequency Vertical:	48 ~ 180Hz	
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)	VIDEO INPUT	TMDS - HDMI (v1.4), PCI-E -	
Pixel Size:	0.275 mm (H) x 0.275 mm (V)	Digital Sync:	DisplayPort (v1.4)	
Surface Treatment:	Anti-Glare, Hard Coating (3H)	ERGONOMICS		
COMPATIBILITY		Tilt (Forward/Back):	-5° / 20°	
PC Resolution (max):	1920x1080	WEIGHT (IMPERIAL)		
Mac® Resolution (max):	1920x1080	Net (lbs):	7.1	
PC Operating System:	Windows 10/11 certified; macOS tested	Net Without Stand (lbs):	6.1	
Mac® Resolution (min):	1920x1080	Gross (lbs):	9.3	
CONNECTOR		WEIGHT (METRIC) Net (kg):	3.2	
3.5mm Audio Out:	1	Net (kg): Net Without Stand (kg):	2.8	
HDMI 1.4:	2	Gross (kg):	4.2	
DisplayPort:	1	DIMENSIONS (IMPERIAL) (W		
Power in:	DC Socket (Center Positive)	Packaging (in.):	23.8 x 15.7 x 4.7	
		Physical (in.):	21.3 x 16.2 x 7.1	
		Physical Without Stand (in.):	21.3 x 12.7 x 1.7	
		DIMENSIONS (METRIC) (WXI		
		Packaging (mm):	605 x 400 x 120	
		Physical (mm):	542 x 412 x 180	

 ${\it Copyright @ ViewSonic Corporation 2000-2024. All rights reserved.}$

2 of 2